

Mini Excavator

Compact excavators from 1.2 to 3.5 t, for utility work, landscaping and confined digging.

8

Models

CE

Machinery directive

ISO 9001

Quality management

2009

Founded

MINI EXCAVATOR

XZ12

1.2 t rated · 0.05 m³ bucket



Bucket capacity	0.05 m³
Operating weight	1.2 t
Engine	Yanmar 3TNV70, 10.3 kW
Dig Depth	2374 mm
Width	1150 mm
Tail Swing	Zero tail swing
Transport Length	3144 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME18

1.5 t rated · 0.06 m³ bucket



Bucket capacity	0.06 m³
Operating weight	1.5 t
Engine	Yanmar 3TNV70, 10.3 kW
Dig Depth	2530 mm
Width	1203 mm
Tail Swing	Zero tail swing
Transport Length	3330 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

XZ18

1.8 t rated · 0.07 m³ bucket



Bucket capacity	0.07 m³
Operating weight	1.8 t
Engine	Yanmar 3TNV70, 10.3 kW
Dig Depth	2686 mm
Width	1255 mm
Tail Swing	Zero tail swing
Transport Length	3516 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME18-2

1.8 t rated · 0.07 m³ bucket



Bucket capacity	0.07 m³
Operating weight	1.8 t
Engine	Yanmar 3TNV70, 10.3 kW
Dig Depth	2686 mm
Width	1255 mm
Tail Swing	Zero tail swing
Transport Length	3516 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME22

2.2 t rated · 0.08 m³ bucket



Bucket capacity	0.08 m³
Operating weight	2.2 t
Engine	Kubota V1505, 18.2 kW
Dig Depth	2894 mm
Width	1325 mm
Tail Swing	Conventional tail swing
Transport Length	3764 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME25

2.5 t rated · 0.08 m³ bucket



Bucket capacity	0.08 m³
Operating weight	2.5 t
Engine	Kubota V1505, 18.2 kW
Dig Depth	3050 mm
Width	1378 mm
Tail Swing	Conventional tail swing
Transport Length	3950 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME35

3 t rated · 0.09 m³ bucket



Bucket capacity	0.09 m³
Operating weight	3.0 t
Engine	Yanmar 4TNV88, 22.4 kW
Dig Depth	3310 mm
Width	1465 mm
Tail Swing	Conventional tail swing
Transport Length	4260 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MINI EXCAVATOR

ME40

3.5 t rated · 0.10 m³ bucket



Bucket capacity	0.10 m³
Operating weight	3.5 t
Engine	Yanmar 4TNV88, 22.4 kW
Dig Depth	3570 mm
Width	1553 mm
Tail Swing	Conventional tail swing
Transport Length	4570 mm

SUITED TO Construction · Agriculture · Landscaping · Mining · Utility

Standard build figures. Final specification is confirmed on the order acknowledgement.

MANUFACTURER

Who builds these machines

WyllBell is the export brand of Shandong Mingsheng Machinery Group, founded in 2009.

Frames, masts and counterweights are fabricated in-house; engines, hydraulics and controllers come from named suppliers, disclosed on request.

Machines are shipped to more than 150 countries. Every unit is load-tested before packing, and a test record travels with the machine.

Founded	2009
Certification	CE (machinery directive), ISO 9001
Export markets	150+ countries and regions
OEM / ODM	Available: paint, decals, nameplate, packaging
Spare parts	Wear parts stocked for every model sold
Factory visit	Welcome; pickup from Jinan or Qingdao arranged

Specifications are the standard build and may be changed at order. Figures are subject to confirmation on the order acknowledgement.